



## PW-50-762 Single

Pentair Water Softener 50 Liters with Autotrol 255 valve and salt tank. The Softener is fitted with a valve and controller made by Pentair Water - Autotrol with highly resistant Noryl and very reliable electronic controls. All food grade certified materials

Regeneration of the softener is programmable volumetric - timed delayed. Regeneration is automatic and can be programmed to take place when the facility is not operating

**Resin Volume :** 50Liters

**Resin Vessel :** 10" Dia. x 55" High Certified NSF44 and PED 97/23/EC

**Working Flow rate :** 2.2 m<sup>3</sup>/hour at zero Hardness out

**Maximum Flow :** 4 m<sup>3</sup>/hour at 1.5 bar pressure drop

**Capacity :** Soft water at zero hardness between two regenerations 12m<sup>3</sup> with incoming water hardness 250 ppm

**Operating Pressure :** 1.4 bar-6.2 bar Valve ,Tank Max Operating Pressure 10 Bar

**Salt Tank :** 100 Liters with brine float valve 75 kg salt capacity

**Connections :** 1" In-Out , Drain 1/2".

**Requires :** Waste drain, and 13A 240 volt electrical socket.

**Certified :** WQA-NSF/ANSI std 44, std 61 and std 372



Autotrol 255 Valve



Logix 762 Volumetric Control